

Method for coating synthetic articles and lacquer to be used for this method.

Patent Number: ☐ EP0450625, B1
Publication date: 1991-10-09
Inventor(s): HOERTH FRANZ-JOSEF DR (DE); ROSE KLAUS DR (DE)
Applicant(s): FRAUNHOFER GES FORSCHUNG (DE)
Requested Patent: ☐ DE4011045
Application Number: EP19910105356 19910404
Priority Number(s): DE19904011045 19900405
IPC Classification: B05D3/00; C09D183/07; C09D183/08
EC Classification: B05D7/02, C08G77/58, C09D183/08, C09D183/14
Equivalents: ☐ WO9303088
Cited Documents: GB2137648; EP0358011; DE3100555; EP0171493

Abstract

The invention relates to a process for coating a plastic substrate in which a paint (varnish) prepared by hydrolytic condensation of one or more hydrolysable silicon compounds in which from 1 to 40 mol% of all Si bonded groups are non-hydrolysable groups containing an ethylenically unsaturated bond, and additionally non-hydrolysable groups containing a mercapto radical are present in such an amount that the ratio between ethylenically unsaturated bonds and mercapto radicals is from 25:1 to 1:1, is applied to the plastic substrate, the paint is cured by irradiation and optionally post-cured thermally, or the paint is cured thermally. The invention also relates to a paint for use in this process.

Data supplied from the esp@cenet database - I2